Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1-18. (Cancelled)

19. (Currently Amended) A method of processing a continuous audio stream containing human speech from a plurality of speakers related to at least one particular transaction, comprising the steps of:

identifying a known speaker from among the plurality of speakers;

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

determining whether a recognized speaker is a predetermined speaker; and

transcribing at least part of the continuous audio stream <u>only</u> if the <u>known recognized</u> speaker is <u>recognized</u> the predetermined speaker;

wherein <u>said transcribing</u> each speaker is processed using a different dictionary of different speaker-trained data trained by the speaker being transcribed.

- 20. (**Previously Presented**) A method according to claim 19, comprising a further step of protocolling time information for detected speaker changes.
- 21. (**Previously Presented**) A method according to claim 19, wherein the step of detecting a speaker change and/or the step of performing a speaker recognition is/are preceded by a further step of detecting non-speech boundaries between continuous speech segments.
- 22. (**Previously Presented**) A method according to claim 19, wherein the step of detecting a speaker change is accomplished by use of at least one characteristic audio feature, in particular features derived from the spectrum of the audio signal.
- 23. (**Previously Presented**) A method according to claim 19, wherein the step of performing a speaker recognition involves the particular steps of calculating a speaker signature from the audio stream and comparing the calculated speaker signature with at least one known speaker signature.
- 24. (**Previously Presented**) A method according to claim 19 for use in a speech recognition or voice control system comprising at least two speaker-specific speaker models and/or dictionaries, wherein interchanging between the at least two speaker-specific dictionaries is dependent on the detected speaker change and the corresponding recognized speaker.

25. (Currently Amended) A method of processing a continuous audio stream containing human speech of a plurality of speakers related to at least one particular transaction, comprising the steps of:

identifying a known speaker from among the plurality of speakers;

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

determining whether a recognized speaker is a predetermined speaker;

indexing the audio stream with respect to the detected speaker change <u>only</u> if the <u>known</u> recognized speaker is recognized the predetermined speaker;

wherein each speaker said indexing is processed using a different dictionary of different speaker-trained data trained by the speaker being transcribed.

- 26. (**Previously Presented**) A method according to claim 25, comprising a further step of protocolling time information for detected speaker changes.
- 27. (**Previously Presented**) A method according to claim 25, wherein the step of detecting a speaker change and/or the step of performing a speaker recognition is/are preceded by a further step of detecting non-speech boundaries between continuous speech segments.

- 28. (**Previously Presented**) A method according to claim 25, wherein the step of detecting a speaker change is accomplished by use of at least one characteristic audio feature, in particular features derived from the spectrum of the audio signal.
- 29. (**Previously Presented**) A method according to claim 25, wherein the step of performing a speaker recognition involves the particular steps of calculating a speaker signature from the audio stream and comparing the calculated speaker signature with at least one known speaker signature.
- 30. (**Previously Presented**) A method according to claim 25 for use in a speech recognition or voice control system comprising at least two speaker-specific speaker models and/or dictionaries, wherein interchanging between the at least two speaker-specific dictionaries is dependent on the detected speaker change and the corresponding recognized speaker.
- 31. (**Currently Amended**) An apparatus for processing a continuous audio stream containing human speech from a plurality of speakers_related to at least one particular transaction, comprising:

a predeterminer which predetermines at least one known speaker from among the plurality of speakers;

a digitizer which digitizes the continuous audio stream;

a detector which detects speaker changes in the digitized audio stream;

a recognizer which recognizes the predetermined speaker in the audio stream; and

a determiner which determines whether a recognized speaker is a predetermined speaker; and

an initiator which initiates transcription of at least part of the <u>continuous</u> audio stream <u>only if the</u> in case of a detected <u>recognized</u> speaker change and a recognized is the predetermined known speaker;

wherein <u>said transcription</u> each speaker is processed using a <u>different</u> dictionary of <u>different</u> speaker-trained data <u>trained by the speaker being transcribed</u>.

- 32. (**Previously Presented**) An apparatus according to claim 31, further comprising a detector which detects non-speech boundaries between continuous speech segments.
- 33. (**Previously Presented**) An apparatus according to claim 31, further comprising a scanner which automatically scans a continuous audio record, in particular a continuous audio stream recorded on a data or a signal carrier, and for detecting speaker changes in the continuous audio record.
- 34. (**Previously Presented**) An apparatus according to claim 31, further comprising a monitor which continuously monitors a real-time continuous audio stream and performing the steps of

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

transcribing at least part of the continuous audio stream if a predetermined speaker is recognized.

35. (**Previously Presented**) An apparatus according to claim 31, further comprising a monitor which continuously monitors a real-time continuous audio stream and performing the steps of

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

indexing the audio stream with respect to the detected speaker change if a predetermined speaker is recognized.

- 36. (**Previously Presented**) An apparatus according to claim 31, further comprising a logging device which protocols time information for the at least one detected speaker change.
- 37. (**Previously Presented**) An apparatus according to claim 31, comprising a marking device which marks at least the beginning of a detected speech segment related to a predetermined speaker.
- 38. (**Previously Presented**) An apparatus according to claim 31, comprising data base which stores speech signatures for at least two speakers.

39. (**Currently Amended**) An apparatus for processing a continuous audio stream containing human speech from a plurality of speakers related to at least one particular transaction, comprising:

a predeterminer which predetermines at least one known speaker from among the plurality of speakers;

a detector which detects speaker changes in the audio stream;

a digitizer which digitizes the continuous audio stream;

a recognizer which recognizes the predetermined speaker in the <u>digitized</u> audio stream;

and

and

a determiner which determines whether a recognized speaker is a predetermined speaker;

an indexer for indexing <u>at least part of the continuous</u> audio stream <u>only if the recognized</u> dependent on a detected speaker <u>is the change and a recognized</u> predetermined <u>known</u> speaker;

wherein <u>said indexing</u> each speaker is processed using a <u>different</u> dictionary of <u>different</u> topics speaker-trained data trained by the speaker being transcribed.

40. (**Previously Presented**) An apparatus according to claim 39, further comprising a detector which detects non-speech boundaries between continuous speech segments.

Atty. Docket No. DE920000055US1 (590.080)

- 41. (**Previously Presented**) An apparatus according to claim 39, further comprising a scanner which automatically scans a continuous audio record, in particular a continuous audio stream recorded on a data or a signal carrier, and for detecting speaker changes in the continuous audio record.
- 42. (**Previously Presented**) An apparatus according to claim 39, further comprising a monitor which continuously monitors a real-time continuous audio stream and performing the steps of

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

transcribing at least part of the continuous audio stream if a predetermined speaker is recognized.

43. (**Previously Presented**) An apparatus according to claim 39, further comprising a monitor which continuously monitors a real-time continuous audio stream and performing the steps of

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

indexing the audio stream with respect to the detected speaker change if a predetermined speaker is recognized.

- 44. (**Previously Presented**) An apparatus according to claim 39, further comprising a logging device which protocols time information for the at least one detected speaker change.
- 45. (**Previously Presented**) An apparatus according to claim 39, comprising a marking device which marks at least the beginning of a detected speech segment related to a predetermined speaker.
- 46. (**Previously Presented**) An apparatus according to claim 39, comprising data base which stores speech signatures for at least two speakers.

47. (Cancelled)

48. (**Currently Amended**) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for processing a continuous audio stream containing human speech from a plurality of speakers related to at least one particular transaction, said method comprising the steps of:

identifying a known speaker from among the plurality of speakers;

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

determining whether a recognized speaker is a predetermined speaker; and

transcribing at least part of the continuous audio stream <u>only</u> if the <u>known</u> <u>recognized</u> speaker is <u>recognized</u> the <u>predetermined speaker</u>;

wherein <u>said transcribing</u> each speaker is processed using a different dictionary of different speaker-trained data <u>trained</u> by the speaker being transcribed.

49. (**Currently Amended**) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for processing a continuous audio stream containing human speech from a plurality of speakers related to at least one particular transaction, said method comprising the steps of:

identifying a known speaker from among the plurality of speakers;

digitizing the continuous audio stream;

detecting a speaker change in the digitized audio stream;

performing a speaker recognition if a speaker change is detected; and

determining whether a recognized speaker is a predetermined speaker;

indexing the audio stream with respect to the detected speaker change <u>only</u> if the <u>known</u> recognized speaker is recognized the predetermined speaker;

wherein <u>each speaker said indexing</u> is processed using a <u>different</u> dictionary of <u>different</u> speaker-trained data <u>trained by the speaker being transcribed</u>.